Mechanically Jointed Rodless Cylinder/Cam Follower Guide Type


Series MY2C 016, 025, 040




Actuators

Modular F.R.L. Pressure Control Equipment

Construction





* The numbers are the same as the "Construction" of the Best Pneumatics No.2 Series MY2C.

Replacement Parts: Seal Kit

No.	Description	Qty.	MY2C16G	MY2C25G	MY2C40G	Note	
14	Seal belt	1	MY16-16A-Stroke	MY25-16A-Stroke	MY40-16A-Stroke		
15	Dust seal band	1	MY2H16-16B-Stroke	MY2H25-16B-Stroke	MY2H40-16B-Stroke		
53	O-ring	2	KA00309	KA00309	KA00320	14, 15 and 53 are not included in the seal kit. Order them as required with by individual part numbers.	Ctual
			(ø4 x ø1.8 x ø1.1)	(ø4 x ø1.8 x ø1.1)	(ø7.15 x ø3.75 x ø1.7)		
22	Scraper	2	MY2B16-PS	MY2B25-PS	MY1B40-PS		1
49	Piston seal	2					\leq
50	Cushion seal	2					
51	Tube gasket	2					
52	O-ring	4					

* Seal kit includes 2, 49, 50, 51 and 52. Order the seal kit based on each bore size.

* Seal kit includes a grease pack (10 g).

When (1) and (15) are shipped as single units, a grease pack (10 g per 1000 strokes) is included. Order with the following part number when only the grease pack is needed.

Grease pack part no.: GR-S-010 (10 g), GR-S-020 (20 g)